





## Declaration of Performance

### Nr. SEPTIC-2014-07-10

|  |   |          |         |  |   |         |         |
|--|---|----------|---------|--|---|---------|---------|
| 1. Unique identification code of the product type  | S 9020, S 9023, S 9030, S 9050, S 9070, S 90100, S 90150, S 90200<br>SR 9060, SR 90120<br>FS 9010, FS 9015, FS 9020, FS 9030, FS 9040, FS 9050, FS 9060 |          |         |  |   |         |         |
| 2. Product serial number   | Each product is fitted with a serial number   |          |         |  |   |         |         |
| 3. Intended use  | Domestic sewage treatment system  |          |         |  |   |         |         |
| 4. Manufacturer  | ESEP Milieutechniek BV<br>Celsiusstraat 20<br>6003 DG Weert<br>The Netherlands  |          |         |  |   |         |         |
| 5. Authorised representative   | Not applicable  |          |         |  |   |         |         |
| 6. System of assessment of performance   | System 4  |          |         |  |   |         |         |
| 7. Reference harmonised standard   | Not applicable  |          |         |  |   |         |         |
| 8. European technical assessment   | Not applicable  |          |         |  |   |         |         |
| 9. Declared performance  | NEN-EN 12566-1:2000   |          |         |  |   |         |         |
| Essential characteristic / performance:  | S 9030  | S 9050   | S 9070  | S 90100  | S 90150   | S 90200 |         |
| Nominal capacity   | 2,4 m3  | 4,2 m3   | 6,3 m3  | 8,2 m3   | 12,2 m3   | 16,9 m3 |         |
| Water tightness  | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    |         |
| Crushing resistance  | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    |         |
| Durability   | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    |         |
| Hydraulic efficiency   | < 2 g   | < 2 g    | < 2 g   | < 2 g  | < 2 g   | < 2 g   |         |
| Essential characteristic / performance:  | SR 9060   | SR 90120 | FS 9020 | FS 9030  | FS 9040   | FS 9050 | FS 9060 |
| Nominal capacity   | 2,4 m3  | 4,2 m3   | 2 m3    | 3 m3   | 4 m3  | 5 m3    | 6 m3    |
| Water tightness  | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    | Pass    |
| Crushing resistance  | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    | Pass    |
| Durability   | Pass  | Pass     | Pass    | Pass   | Pass  | Pass    | Pass    |
| Hydraulic efficiency   | < 2 g   | < 2 g    | < 2 g   | < 2 g  | < 2 g   | < 2 g   | < 2 g   |
| 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9, provided that transported, installed and maintained as described in user manual. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. |   |          |         |  |   |         |         |
| Weert, 2014-07-10  |   |          | signed: |  | Bruschinski  |         |         |